



MACH III

High Velocity Air Blower

Maximum Air Velocity Reduces Dry Time

- Powerful 1 HP motor generates up to 4,100 CFM and will get your floors ready for traffic quicker.
- Pitch the unit at a 45° or 90° angle to circulate airflow or place the machine on the surface (0°) for a more concentrated airflow.
- The interlocking design makes it easy to securely stack multiple machines for increased airflow and easy storage.
- The durable, rotationally-molded, polyethylene housing provides extended life.



Specifications

Product Number	49003
Air Flow (CFM)	Speed 1 - 2,296 Speed 2 - 3,321 Speed 3 - 4,100
Velocity	6,200 ft/min
Motor	1 HP
Housing Construction	Rotationally-molded polyethylene
Fan Construction	Non-corrosive polyethylene
Angle Positions	0°, 45° and 90°
Stackable	Yes, exclusive interlocking design
Sound Level	72 dBA
Power Cable	42 ft
Cable Wrap	Built-In
Dimensions	15" x 17" x 20"
Shipping Weight	33 lbs
UL Approval	Yes
Commercial Warranty	1 year parts & labor with the exception of normal wear parts.

Specifications are subject to change without notice.

Use to Dry:

- Carpeting
- Hard Floors
- Flooded Areas
- Upholstery/Carpeted Walls
- Fresh Paint